

EPSON®

EXCEED YOUR VISION™

Epson AcuLaser C4200 Series

Fast, reliable, high quality A4 colour laser printer

The Epson AcuLaser C4200 Series provides demanding workgroups with fast, professional results in both colour and mono. And with economical running costs, you can add vibrant colour to your documents, whenever you want.

Speed and quality

With a first page out time of 10.2 seconds and print speeds of 35ppm in mono and 25ppm in colour, the Epson AcuLaser C4200 Series won't keep you waiting. The powerful combination of Epson AcuBrite toner and Epson AcuLaser Colour ASIC technology, give you the very best quality results for all your text and images.

Simple integration

The Epson AcuLaser C4200 Series works with all common operating systems and integrates easily with your network and applications.

Flexible and efficient

The Epson AcuLaser C4200 Series prints on a wide range of media and has a large paper capacity, from up to 5 trays. It also provides duplex printing as standard.

Easy to use and maintain

The Epson AcuLaser C4200 Series is easy to maintain, with reliable and long-lasting consumables. It also has a large graphic LCD control panel that gives you all the information you need to get the best from your printer.

Key features

- High speed printing: 35ppm mono/ 25ppm colour
- Accurate, consistent and economical output with Epson AcuBrite toner and Epson AcuLaser Colour 4800RIT*
- Large paper capacity: min 700 sheets. Max 2350 from 5 trays
- Monthly print volume of 90,000 pages
- Comprehensive connectivity: Parallel, Hi-Speed USB (2.0 compatible) and 10/100 Base Tx Ethernet
- Supports PCL5C**, Epson ESC/Page, ESC/P2, FX, IBM 1239X and Adobe® PostScript® Level 3
- Easy to maintain, pre-installed toners



* Resolution Improvement Technology

** Epson AcuLaser C4200DNPC5 and C4200DTNPC5

Model	Epson AcuLaser C4200DN (Standard model)	Ordering Information
Key Features Printing Technology Resolution Print Speed First Page Out Processor Memory: Standard / Maximum LCD Maximum Monthly Volume	Laser Single Pass Epson AcuLaser Colour 4800 RIT* (*Epson AcuLaser Resolution Improvement Technology) Up to 35ppm in Monochrome, up to 25ppm in Colour (A4). Up to 20.4ppm in Duplex 10.2 seconds PowerPC 600MHz 128MB (Standard) / 640MB (Maximum) 22-digit 5-line backlit LCD 90,000 pages	Epson AcuLaser C4200DN (Standard Model) C11C600001BY Epson AcuLaser C4200DTN (Standard model + 1100 sheet paper cassette) C11C600001BZ Epson AcuLaser C4200DNPC5 (Standard model + PCL5C option) C11C600001BV Epson AcuLaser C4200DTNPC5 (Standard model + 1100 sheet paper cassette unit + PCL5C option) C11C600001BW
Paper Handling Standard Paper Input Paper Size Paper Weight Optional Paper Handling Maximum Paper Input Paper Output (Standard/Maximum)	700 sheets (150 Multi Purpose tray + 550 Standard Universal Cassette, 80g/m ²) A4, A5, B5, LT, GLT, HLT, Executive, F4, LGL13, LGL14; From 90 x 139.7mm to 220 x 355.6mm; 60 to 216 g/m ² 60 - 216 g/m ² 550 Sheet Paper Cassette, 1100 Sheet Paper Cassette (550 x 2) 2350 sheets (150 MP tray + 4 x 550-Sheet Paper Cassette) 250 Sheets (Face Down)	 Epson AcuLaser C4200DTNPC5 (Standard model + 1100 sheet paper cassette unit + PCL5C option) C11C600001BW
Printer Control Language Emulations Standard Optional	ESC/Page™ Colour, ESC/Page, ESC/P2™, FX, IBM Mode I239X, Adobe PS3 PCL5C, PCL6 (Colour - starting from April 2006)	Toner Yellow 0242 C13S050242
Resident Typefaces Scalable BitMap Barcodes	84 ESC/Page, 17 PS3, 10 ESC/P2, 8 I239X, 93 PCL5c 7 ESC/Page, 7 PCL5c** Code39, Code128, Interleaved 2of5, UPC-A, UPC-E, EAN-8, EAN-13, Codabar ** Epson AcuLaser C4200DNPC5 and C4200DTNPC5 models only	Toner Magenta 0243 C13S050243 Toner Cyan 0244 C13S050244
Connectivity Interfaces Network Printing Protocols Network Management Protocols	IEEE 1284 parallel interface (Compatibility, Nibble and ECP mode), Hi-Speed USB (2.0HS, D4) 10/100 Base Tx ethernet interface, Optional Type-B I/F (Level 3) TCP/IP: LPR, FTP, IPP, PORT2501, PORT9100 Microsoft Network: NetBIOS over TCP/IP, NetBIOS over NetBEUI; Netware - Operating mode: Standby (factory default), NDS Print Server, Bindery Print Server, Remote Printer; AppleTalk TCP/IP: SNMP, HTTP, TELNET, DHCP, BOOTP, APIPA, PING, DDNS, Rendezvous (mDNS), SNT, SSDP. NetBEUI: SNMP; NetWare and AppleTalk: SNMP	Toner Black 0245 C13S050245 Photoconductor Unit 1109 C13S051109 Fuser Unit C13S053021
Consumables ⁽¹⁾ Toner Toner Save Mode Photoconductor Unit Transfer Unit Fuser Unit	K: 10,000 pages ⁽¹⁾ , CMY: 8,500 pages ⁽¹⁾ Yes 35,000 pages ⁽¹⁾ 35,000 pages ⁽¹⁾ 100,000 pages	Transfer Belt C13S053022 550 Sheet Paper Cassette Unit C12C802251
Power Requirements Rated Voltage/Frequency/Current Power Consumption	Energy Star compliant 220 or 240V ± 10% / 50 or 60Hz ±3Hz / 5A Operating: 960W max, 329/409W average (Colour/BW). Standby: 71W; Sleep: 25W; Off: 0W	1100 Sheet Paper Cassette Unit C12C802261
Minimum Recommended System Requirements PC/MAC PC Interfaces MAC Interfaces Operating System	OS recommended requirements IEEE1284 ECP mode, 10/100BaseTx Ethernet, USB (Microsoft® Windows® 98/ME/2000/XP only) 10/100BaseTx Ethernet, USB Microsoft® Windows® 98/Me/XP/2000/Server 2003; Mac OSX 10.1.2 or later	37.2 GB Hard Disk Drive C12C824172
Dimensions & Weight* (WxDxH) * Weight including consumables	Epson AcuLaser C4200DN 437 x 588 x 457 mm, 34.5 Kg Epson AcuLaser C4200DTN 584 x 695 x 796 mm, 56 Kg	
Environmental Conditions Temperature Humidity Sound Power Sound Pressure	Operating: 10 to 32 degC; Stopped: -20 to 40 degC; Storage: 0 to 35 degC; No condensation Operating: 15 to 85 %; Stopped: 5 to 85 %; Storage: 15 to 80%; No condensation Operating: 6.65B; Standby: 5.0B; Sleep: Background Noise Operating: 55 dB; Standby: 35dB; Sleep: Background Noise	
Safety and Regulations Safety Standards EMC/EMI	IEC60950 3rd Edition; EN60950 3rd Edition; IEC60825 Class 1 Laser Product; CE Directive; Nordic Agency Approvals EN55022 (CIRSPR Publication22), Class B; EN61000-3-2 (Harmonics) Class A; EN61000-3-3 (Flicker)	
Warranty* Standard/Optional	1 year on-site/Epson CoverPlus+ 3 year extended Warranty On-site	

⁽¹⁾ The above figures are approximate and are based on the number of A4 sheets printed at 5% coverage under conditions of continuous printing. Intermittent use may reduce page yield.
*Warranty offers are not available in all countries. Please contact your local Epson representative for more information.



For further information please contact your local Epson office or visit www.epson-europe.com

Austria 0810/20 01 13 (0,07 €/Min.) **Belgium** 070/350120 (0.1735 €/Min.) **Czech** 800 / 142 052 **Denmark** 44 50 85 85 **Finland** 0201 552 091

France 0892 899 999 (0,34 €/min) **Germany** 01805/23 41 10 (0,12 €/Min.) **Greece** 210-6244314 **Hungary** 06800 147 83 **Italy** 02-660321 10

(0,12 €/Min.) **Luxemburg** 900/43010 (0,24 €/mn.) **Middle East** +9714 8818934 **Netherlands** 0900-5050808 (0.05 €/oproep + 0.15 €/Min.)

Norway 22 06 42 80 **Poland** 0-0-800 4911299 (0,16 zł/min.) **Portugal** 707 222 111 **Russia** (095) 777-03-55 **Slovakia** 0850 111 429

South Africa (+2711) 465-9621 **Spain** 93 582 15 00 **Sweden** 077-140 01 35 **Switzerland** 0848 448820 (4-8 cent./mn.) **Turkey** (0212) 3360303

EPSON® is a registered trademark of SEIKO EPSON® Corporation. All other product names and other company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice.

Entity carrying out management and coordination pursuant to article 2497 bis of Civil Code: Epson Europe BV